

# Excavator attachments


Demolition, recycling and earth-moving.  
Experience our Hydraulic Attachment Tools.



# Turn up the volume

Our Multi Grapples are ideal for loading and sorting various materials as well as demolishing wooden and masonry structures.

360° endless **hydraulic rotation** allows optimal positioning and precise handling.



Solid **perforated shells** provide excellent visibility during operations.


<b>MG range</b>		<b>MG 100</b>	<b>MG 200</b>	<b>MG 300</b>	<b>MG 400</b>	<b>MG 500</b>	<b>MG 800</b>	<b>MG 1000</b>
Carrier weight class <sup>1)</sup>	t	0.7 – 1.2	1.2 – 3	2 – 5	4 – 8	5 – 9	10 – 16	12 – 20
Service weight <sup>2)</sup>	kg	90	175	290	450	460	825	1,150
Product weight	kg	71	155	255	384	396	752	966
<b>A</b>	mm	620	630	750	880	880	1,150	1,265
<b>B</b>	mm	600	900	1,187	1,480	1,585	1,791	1,900
<b>C</b>	mm	310	450	500	600	700	800	800
<b>F1</b>	t	0.6	1.5	2.0	2.3	2.4	3.8	4.6
Loading volume	m <sup>3</sup>	0.02	0.05	0.11	0.21	0.25	0.35	0.49
Oil flow rate (opening & closing)	l/min	10 – 15	15 – 25	25 – 35	35 – 50	35 – 50	70 – 100	85 – 120
Max. operating pressure (opening & closing)	bar	300	300	300	300	300	350	350
Oil flow rate (rotation)	l/min	3 – 5	5 – 10	5 – 10	10 – 15	10 – 15	20 – 25	20 – 25
Max. operating pressure (rotation)	bar	170	170	170	170	170	170	170



Our Multi Grapples handle any material with utmost precision. They deliver a steady grip and virtually constant closing force.




Cutting blades are both replaceable and reversible.



Optional **tooth blades** for block and stone handling (MG 400 – 1500).



Optional **bolt-on side plates** for handling fine-grained material and debris (MG 400 – 1500).



MG range		MG 1500	MG 1800	MG 2300	MG 2700	MG 3000	MG 5000
Carrier weight class <sup>1)</sup>	t	16 – 24	20 – 28	25 – 38	28 – 50	35 – 50	45 – 100
Service weight <sup>2)</sup>	kg	1,700	1,800	2,280	2,750	3,250	5,300
Product weight	kg	1,485	1,619	2,080	2,574	3,000	5,000
<b>A</b>	mm	1,500	1,500	1,450	1,635	1,800	2,000
<b>B</b>	mm	2,100	2,100	2,300	2,270	2,460	3,000
<b>C</b>	mm	1,020	1,200	1,200	1,200	1,500	1,500
<b>F1</b>	t	6.8	6.8	8.0	9.0	9.0	13.0
Loading volume	m <sup>3</sup>	0.73	0.86	0.88	0.92	1.30	1.60
Oil flow rate (opening & closing)	l/min	120 – 170	150 – 170	160 – 180	180 – 200	180 – 200	280 – 300
Max. operating pressure (opening & closing)	bar	350	350	350	350	350	350
Oil flow rate (rotation)	l/min	30 – 35	30 – 35	30 – 35	30 – 35	30 – 35	50 – 60
Max. operating pressure (rotation)	bar	170	170	170	170	210	210

<sup>1)</sup> Weights apply to standard carriers only. Any variances must be agreed with Epiroc and/or the carrier manufacturer prior to attachment.

<sup>2)</sup> Attachment with average-sized adapter plate.

# United in performance. Inspired by innovation.

Performance unites us, innovation inspires us, and commitment drives us to keep moving forward. Count on Epiroc to deliver the solutions you need to succeed today and the technology to lead tomorrow.  
**[epiroc.com](http://epiroc.com)**

