



PLANER WITH CONVEYOR BELT

PERFORMER



FEATURES

Hydraulic side shift, hydraulic independent right and left depth adjustment and manual tilt are included. Self-leveling for constant planing depth. Patented, built in performer gauge aids in maximizing production.

DRUMS

Asphalt drum included and concrete drum available for specialty applications.

DISCHARGE BELT

The belt can work in either direction, variable speed adjustment or turned off completely if needed for traditional use.

	PLC 18	PLC 24	PLC 30	PLC 40	
WIDTH	18	24	30	40	inch
MAX. DEPTH	6	7	7	5	inch
DEPTH ADJUST.	Independent left and right, hydraulic/manual optional				
SIDE SHIFT	Hydraulic				
TRANSVERSE TILT	Built in				
TILT	16°				
WEIGHT	2080	2400	2650	3000	lbs
FLOW	24 - 31	29 - 38	32 - 42	32 - 42	gpm
PRESSURE	4300 - 2400	4300 - 2400	4300 - 2400	4300 - 2400	psi



PLANER WITH CONVEYOR BELT

PERFORMER



MARKET-LEADING FUNCTIONALITY

The milling depth remains constant regardless of changing surfaces or the irregular movement of the prime mover. Operator inconsistencies are all but eliminated.

SIMEX PATENT

The skis move independently of each other and precisely follow the surface to the right or left. The independent depth adjustment on RH and LH sides combined with the self-leveling system achieves smooth operation. Innovations in the Simex patented self-level lead to precise, accurate, and efficient planing.

DRY CUTTING FOR HIGH FLOW AND STD FLOW SKID STEERS

