


# special | drum cutters



## ER 3000

Transverse drum cutters  
for excavators from 99,000 to 154,000 lbs (45 to 70 tons)

<b>ER 3000</b> Transverse cutter Standard	Unit	Model <b>ER 3000-1</b>	Model <b>ER 3000-2</b>	Model <b>ER 3000-3</b>
Recommended rotation speed	RPM	62	57	53
Recommended oil flow at 725 psi	gal/min	92.5	105.6	118.9
Torque at 5,000 psi	lbf-ft	22,990	28,730	34,585
Cutting force at 5,000 psi	lbf	17,410	21,755	26,190
Weight	lbs	7,275	7,275	7,275



Max. Oil flow: 158 gal/min  
Max hydraulic pressure: 5,000 psi  
Recommended min. Hydraulic operating pressure: 4,350 psi  
Rated power: 268 hp

Maximum oil flow and pressure figures shown in the table above cannot be achieved at the same time.  
Contact Drumcutters to discuss hydraulic requirements once actual site conditions are known.

## accessories ER 3000



**Standard**  
Round attack pick  
**ER 25/77/80/38-30 Q**  
Part No.  
25 77 80 35 E

Applications:  
Concrete, medium hard  
and hard rock

**QuickSnap**  
**QS 5000**  
Part No.  
99 50 00 30



Round attack pick  
**ER 25/100/80/38-30 Q**  
Part No.  
25 100 80 35 E

Applications:  
Salt, gypsum, middle hard,  
fractured rock

**QuickSnap**  
**QS 5000**  
Part No.  
99 50 00 30



Pick box  
**PH 5300**  
Part No.  
75 30 10